

PCI-1730U


PCI-1733

PCI-1734

**32-ch Isolated Digital I/O
Universal PCI Card**

32-ch Isolated Digital Input PCI Card

32-ch Isolated Digital Output PCI Card



Features

- ISA-compatible with PCL-730/733/734
- 32-ch isolated DI/O (16-ch digital input, 16-ch digital output)
- 32-ch TTL DI/O (16-ch digital input, 16-ch digital output) (PCI-1730U only)
- High output driving capacity
- Interrupt handling capability
- 2 x 20-pin connectors for isolated DI/O channels (PCI-1730U only)
- 2 x 20-pin connectors for TTL DI/O channels (PCI-1730U only)
- D-type connector for isolated input and output channels
- High-voltage isolation on output channels

Introduction

PCI-1730U, PCI-1733, and PCI-1734 offer isolated digital input channels as well as isolated digital output channels with isolation protection up to 2,500 V_{DC}, which makes them ideal for industrial applications where high-voltage isolation is required. There are also 32 TTL digital I/O channels on PCI-1730U.

Specifications

Digital Input (PCI-1730U only)

- **Channels** 16 (16-ch/group)
- **Compatibility** 5 V/TTL
- **Input Voltage** Logic 0: 0.8 V max.
Logic 1: 2.0 V min.
- **Interrupt Capable Ch.** 2 (DI0, DI1)

Isolated Digital Input (PCI-1730U/ PCI-1733)

- **Channels** 16 (16-ch/group)
- **Input Voltage** Logic 0: 1 V max. (2 V max.)
Logic 1: 5V min. (30 V max.)
- **Interrupt Capable Ch.** 2 (IDI0, IDI1)
- **Isolation Protection** 2,500 V_{DC}
- **Opto-Isolator Response** 25 μs
- **Input Resistance** 2.7 kΩ @ 1 W

Digital Output (PCI-1730U only)

- **Channels** 16 (16-ch/group)
- **Compatibility** 5 V/TTL
- **Output Voltage** Logic 0: 0.8 V max.
Logic 1: 2.0 V min.
- **Output Capability** Sink: 24 mA
Source: 15 mA

Isolated Digital Output (PCI-1730U/ PCI-1734)

- **Channels** 16 (16-ch/group)
- **Output Type** Sink type (NPN)
- **Isolation Protection** 2,500 V_{DC}
- **Output Voltage** 5 ~ 40 V_{DC}
- **Sink Current** PCI-1730U: 300 mA max./channel
PCI-1734: 200 mA max./channel
- **Opto-Isolator Response** 25 μs

General

- **Bus Type** PCI V2.2 (Universal PCI V2.2 for PCI-1730U)
- **I/O Connectors** 1 x DB37 female connector
4 x 20-pin box header (1730U only)
- **Dimensions (L x H)** 175 x 100 mm (6.9" x 3.9")
- **Power Consumption** Typical: 5 V @ 250 mA, 12 V @ 35 mA
Max.: 5 V @ 400 mA, 12 V @ 60 mA
- **Operating Temperature** 0 ~ 60° C (32 ~ 140° F)
- **Storage Temperature** -25 ~ 85° C (-13 ~ 185° F)
- **Storage Humidity** 5 ~ 95% RH, non-condensing (see IEC 68-2-3)

Ordering Information

- **PCI-1730U** 32-ch Isolated Digital I/O Univ. PCI Card
- **PCI-1733** 32-ch Isolated Digital Input PCI Card
- **PCI-1734** 32-ch Isolated Digital Output PCI Card

Accessories

- **PCL-10120-1** 20-pin Flat Cable, 1 m
- **PCL-10120-2** 20-pin Flat Cable, 2 m
- **ADAM-3920** 20-pin DIN-rail Flat Cable Wiring Board
- **PCLD-782** 16-ch Isolated DI Board w/ 1m 20-pin Flat Cable
- **PCLD-885** 16-ch Power Relay Board w/ 20p & 50p Flat Cables
- **PCLD-785** 16-ch Relay Board w/ One 1m 20-pin Flat Cable
- **ADAM-3937** DB37 DIN-rail Wiring Board
- **PCL-10137-1** DB37 Cable, 1 m
- **PCL-10137-2** DB37 Cable, 2 m
- **PCL-10137-3** DB37 Cable, 3 m